

I DEAL SOLUTION FOR PORTABLE PRINTING



# MOBILE PRINTER

## LK-P20

- Durable and robust with rugged design
- Magnetic stripe reader & smart card reader (Option)
- Standard interface RS-232C, USB and optional Bluetooth or Wi-Fi(802.11b/g) available.
- Prints at 80mm per second
- Fast AC charger and long life battery : 2.5Hrs charging time, 17Hrs stand-by
- Optional accessories :  
leather case, shoulder strap, cradle and vehicle charger(12/24V)
- Various O/S drivers : Win CE/Mobile, Symbian, Linux, Blackberry





## ● SPECIFICATION

ITEM		TYPE
MODEL		LK-P20
PRINTING	METHOD	Direct Thermal
	SPEED	80mm / sec
DOT DENSITY		203 DPI
DOT PITCH		8dots /mm, 0.125 pitch
EFFECTIVE PRINTING WIDTH		48mm, 384dots/line
CHARACTER PER LINE		Font A(12 x 24) 32 columns Font B(9 x 17) 42 columns
PAPER	TYPE	Thermal Paper
	WIDTH	58mm
	THICKNESS	0.06mm ~ 0.09mm
	ROLL DIAMETER	Max. ø 48mm
RELIABILITY	ROLL CORE INNER	12.5mm ± 0.5mm
	TPH LIFE	50km
CHARACTER SET	PULSE ACTIVATION	50,000,000pulse or more (12.5% Print Ratio)
	ALPHA NUMERIC CHARACTER	95
	EXTENDED GRAPHIC INTERNATIONAL CHARACTER	128 x 18page(1 space page) 14
BARCODE		EAN-8, EAN-13, Code 39, ITF, UPC-A, UPC-E, Codabar, Code 93, Code 128, PDF 417(2D), QR Code(2D), Maxicode(2D)
EMULATION		ESC/POS Command compatible
DRIVER		Window Printer Driver(7, XP, 2000, 2003, VISTA, 32 & 64bit), Windows (CE 4.2 & 5.0 / Mobbile 5.0), Linux Printer Driver Symbian, Blackberry
SENSOR		Paper end sensor
INTERFACE	STANDARD	Serial(RS-232C), USB
	OPTION	Bluetooth class 2, Wi-Fi (802.11b/g)
BATTERY CHARGER		External Charger (Output 8.4VDC/0.8A)
BATTERY		7.4V 1800mAh Li-ion, 2.5Hrs Charging Time 16Hrs stand-by
DIMENSION		96mm x 136mm x 58mm (W x D x H)
WEIGHT		450g (With Battery)
TEMPERATURE	OPERATION	-10 ~ 50°C
	STORAGE	-20 ~ 60°C
HUMIDITY	OPERATION	35 ~ 80%
	STORAGE	10 ~ 90%

### MSR



### ACCESSORIES



CASE



CRADLE



STRAP



## SEWOO TECH Co., Ltd.

374-2, Gajang-dong, Osan-si, Gyeonggi-do, 447-210, Korea

T. +82-31-459-8200 F. +82-31-459-8880

www.miniprinter.com